


S6B3-T2MPTK2LZ (PACKAGE)
 378 - 448 kW | PROPULSION
 IMO TIER II

MITSUBISHI MARINE ENGINE

RELIABLE MECHANICAL ENGINE



ENGINE DATA

Engine model	S6B3-T2MPTK2LZ (package)
Cylinder configuration	6 in-line
Total displacement	14.6
Bore x stroke (mm)	135 x 170
Flywheel and housing	SAE 14 / SAE 10
Compression ratio	14.2:1
Dry weight (kg)	1400

Method of operation

4-stroke, water-cooled diesel engine, with direct-injection, turbocharger, air-cooler, built-up heat exchanger and sea water pump

Cooling method

separate high and low temperature cooling circuit; charge air cooler directly cooled by sea water (intercooler)

RATING^{1,2}

Rating	HD	MD
Output (kW)	378	448
Output (bhp)	507	601
Engine speed (rpm)	2001	2001
Emissions	IMO Tier II	

¹ For rating definitions, please see our website.

² Atmospheric condition: barometric pressure: 100kPa, ambient temperature: 298K, relative humidity: 30%.

STANDARD AND OPTIONAL EQUIPMENT

STANDARD EQUIPMENT

Governor (mandatory)

- Mechanical governor, RSUV type

Fuel system

- Flexible fuel supply - and return hoses
- Fuel feed pump
- Fuel fine filters, change-over type
- Fuel injection pump
- Dual walled high-pressure fuel lines including alarm switch fuel leakage
- Fuel injectors
- Fuel oil / water separator (filter)

Lubricating oil system

- Oil drain connection
- Wet type oil pan with inspection covers
- Oil pressure pump, gear driven
- Lubricating oil filters, change-over type
- By-pass filter
- Oil cooler with thermostat
- Piston cooling through oil injectors
- Lubricating oil drain pump (wing pump)

Starting and electrical system

- Electric starter (Earth floated 24V)
- Alternator
- Stop solenoid (ETS)
- Battery switch

Cooling system

- Heat exchanger / header tank, mounted on engine, including piping and level switch and seawater pump (TK)
- Flexible pipe sets for seawater
- Sea water filter

Air inlet system

- Mitsubishi turbocharger
- Air inlet silencer with pre-cleaner
- Inlet air aftercooler or intercooler
- Inlet manifolds or ducts

Exhaust system

- Flexible expansion joint

Other

- Mounting brackets for rigid mounting
- Flywheel and housing, SAE standard
- Torsional vibration damper

Monitoring system



- Monitoring system (incl. sensors on engine, wiring to junction box, 1 x engine room panel, 1 wheel house panel).

OPTIONAL EQUIPMENT

Classification

We are cooperating with many of the major classification societies.

DIMENSIONS



More information

Contact your local dealer for more information regarding Mitsubishi Marine Engines and optional equipment or, visit www.mtee.eu